Material Safety Data Sheet



Zep Inc. 1310 Seaboard Industrial Blvd. Atlanta, GA 30318 1-877-I-BUY-ZEP (428-9937) www.zep.com Section 1. Chemical Product and Company Identification

Product name ZEP SHEEN

Product use Furniture Polish & Cleaner

Product code 0216

Date of issue 07/23/08 Supersedes 12/21/04

Emergency Telephone Numbers

For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency

INFOTRAC: (877) 541-2016 Toll Free - All Calls

Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded

In the District of Columbia (202) 483-7616

Printing date: 07/23/08 Prepared By

Compliance Services

1420 Seaboard Industrial Blvd.

Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

WARNING

*Hazard Determination System (HDS): Health, Flammability, Reactivity

CALICEC EVE IDDITATIO

CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

CONTENTS UNDER PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects Routes of Entry Dermal contact. Inhalation.

Eyes Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Inhalation of spray mists or vapors may cause central nervous system depression

irritation. Inflatation of spray firsts of vapors may cause central nervous sy

characterized by headache, dizziness, nausea, and/or stupor.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause

damage.

Chronic effects Prolonged or repeated contact may dry skin and cause irritation.

Carcinogenicity Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
HYDROCARBON PROPELLANT; blend of propane & isobutane	75-28-5; 74-98-6	10 - 20
ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)	64741-73-7	5 - 15
ISOPARAFFINIC SOLVENT; petroleum naphtha, light alkylate	64741-66-8	1 - 10

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and

remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact Flush contaminated skin with plenty of water. Get medical attention if irritation develops.

Inhalation Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be

kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink.

Never give anything by mouth to an unconscious person. Get medical attention immediately.

Page: 1/3

Product code 0216 **Material Safety Data Sheet** Product Name ZEP SHEEN

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)

Not available. **Flash Point**

Flammable Limits Not available.

Non-flammable. (CSMA Method) **Flammability**

CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and Fire hazard

the container may burst, with the risk of a subsequent explosion. Bursting aerosol containers

may be propelled from a fire at high speed.

Fire-Fighting Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to

Procedures fire with water. Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame

> or any other ignition source. Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash thoroughly after handling.

Storage CONTENTS UNDER PRESSURE. Do not puncture, incinerate or store the container at temperatures above 49°C

(120°F) or in direct sunlight. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Exposure limits Product name

HYDROCARBON PROPELLANT; blend of propane & isobutane ACGIH TLV / OSHA PEL (United States). Notes: Propane

TWA: 1000 ppm 8 hour(s). ISOPARAFFINIC SOLVENT; hydrotreated light distillate NIOSH REL (United States). TWA: 1200 mg/m3 Form: Vapor

ISOPARAFFINIC SOLVENT; petroleum naphtha, light alkylate Supplier Suggested TLV (United States).

TWA: 1400 mg/m3 8 hour(s).

Personal Protective Equipment (PPE)

W **Eyes** Safety glasses.

Body For prolonged or repeated handling, use the following type of

gloves: Neoprene gloves. Nitrile gloves. Rubber gloves.

Respiratory Use with adequate ventilation.

Section 9. Physical and Chemical Properties

Physical State Liquid. [Aerosol.] Color Opaque. Emulsion. Odor Pleasant. Lemon-like. pН Not applicable

Boiling Point 104.44°C (220°F) Vapor Pressure Not determined. **Specific Gravity** 0.93 Vapor Density Not determined.

Solubility Insoluble in the following materials: cold water and **Evaporation Rate** 1 (Water = 1)

hot water.

VOC (Consumer) 158 (g/l). 1.3 lbs/gal (17.0%)

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Keep away from heat, sparks and flame. Reactive or incompatible with the following materials:

oxidizing materials and acids.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂)

Section 11. Toxicological Information

Acute Toxicity

Exposure Product/ingredient name Result **Species Dose**

Isoparaffinic Solvent; Hydrotreated light distillate LD50 Dermal Rabbit >2000 mg/kg (petroleum)

LD50 Oral Rat >2000 mg/kg Product code 0216 Material Safety Data Sheet Product Name ZEP SHEEN

Section 12. Ecological Information

Environmental Effects

No known significant effects or critical hazards.

Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations

Waste Information

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-hazardous waste

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	Consumer commodity ORM-D			
IMDG Class	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG*: Packing group

Section 15. Regulatory Information

U.S. Federal Regulations

SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65 No products were found.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.